

Thickness Tolerances for Solid Rubber Sheet

SOLID RUBBER

| THICKNESS INCHES | TOLERANCE +/- |
|---------------------|------------------|
| 1/32" (.032) | .012" |
| 1/16" (.062) | .016" |
| 3/32" (.094) | .016" |
| 1/8" (.125) | .020" |
| 3/16" (.187) | .031" |
| 1/4" (.250) | .031" |
| 5/16" (.312) | .031" |
| 3/8" (.375) | .047" |
| 1/2" (.500) | .047" |
| 5/8" (.625) | .063" |
| 3/4" (.750) | .093" |
| 1" (1.000) | 10% |

WIDTH TOLERANCES FOR SOLID RUBBER STRIPPING/SPLITTING

| MATERIAL WIDTH (INCHES) ABOVE | MATERIAL WIDTH (INCHES) INCLUDING | TOLERANCE +/- |
|----------------------------------|--------------------------------------|------------------|
| 0" | .25" | .016" |
| .25" | .50" | .025" |
| .50" | 1.00" | .040" |
| 1.00" | 2.00" | .063" |
| 2.00" | 4.00" | .080" |
| 4.00" | 8.00" | .100" |
| 8.00" | 16.00" | .125" |
| 16.00" | 32.00" | .160" |



RUBBERMILL

Disclaimer: The information contained in this document is to be used as a guide only. RubberMill cannot guarantee the accuracy, or be held responsible for the information's end use.

Talk to a person... not a machine! • 336-622-1680 • www.rubbermill.com